

Distributed by:



Asian Tyre Sourcing

Guangfa Financial Building - Office # 2504
No. 40 Shandong Road,
Qingdao China 266071s
Tel. China + 86 (532) 85019128
sales@asiantyresourcing.com



ROADSHINE

PASSENGER CAR TYRE



RS901



- Computer optimized pattern pitch provides you with quiet driving experience. Lateral sipe design provides tire with excellent grip performance.
- Rib designed between the circumferential pattern blocks reduces the pattern creep with even tread wear.
- Special groove design reduces stone trapping and improves tire wear.

Benefits



Comfort



Quiet



Economy

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 185R14C-8PR | 102/100Q | 5.5J | 5.0J-6.0J | 450 | 850 | 900 | 650 | 188 | 8.0 |
| 195R14C-8PR | 106/104Q | 5.5J | 5.0J-6.0J | 450 | 950 | 900 | 668 | 196 | 8.0 |
| 195R15C-8PR | 106/104Q | 5.5J | 5.0J-6.0J | 450 | 960 | 900 | 693 | 196 | 8.0 |

RS902



- Suitable for various commercial vehicles, estate cars and pickup trucks etc. 3 longitudinal grooves provides excellent linear driving ability and skid resistance.
- Variable groove design reduces tire noise during driving. Computer-optimized design combine with special rubber formulation provide excellent tire wear resistance.

Benefits



Longer Mileage



Comfort



Quiet

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-----------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 155R13C-8PR | 85/83Q | 4.50B | 4.00B-5.00B | 350 | 517 | 487 | 578 | 157 | 7.0 |
| 165/70R13C-6PR | 88/86T | 5.0J | 4.5J-5.0J | 375 | 560 | 53 | 562 | 170 | 7.6 |
| 165R13C-8PR | 94/93Q | 4.5J | 4.0J-5.0J | 450 | 670 | 650 | 594 | 165 | 7.5 |
| 175R13C-8PR | 97/95Q | 5.00B | 4.50B-5.50B | 450 | 730 | 690 | 610 | 177 | 8.5 |
| 175/70R14C | 95/93T | 5.0J | 4.5J-6.0J | 375 | 690 | 650 | 602 | 177 | 8.5 |
| 215R14C-8PR | 112/110P | 6.0J | 5.5J-7.0J | 450 | 1120 | 1060 | 700 | 216 | 8.5 |
| 185R15C-8PR | 103/102Q | 5.5J | 5.0J-6.0J | 450 | 875 | 850 | 677 | 189 | 8.0 |
| 195/70R15C-8PR | 104/102N | 6.0J | 5.0J-6.0J | 450 | 900 | 850 | 655 | 201 | 8.5 |
| 205/70R15C-8PR | 106/104R | 6.5J | 6.0J-7.0J | 450 | 1120 | 1060 | 697 | 228 | 8.5 |
| 225/70R15C-8PR | 112/110Q | 6.5J | 6.0J-7.0J | 450 | 1120 | 1060 | 697 | 228 | 8.5 |
| 175/75R16C-8PR | 101/99Q | 5.0J | 4.5J-5.5J | 475 | 825 | 775 | 688 | 177 | 8.5 |
| 205/75R16C-8PR | 110/108Q | 5.5J | 5.5J-6.5J | 475 | 1060 | 1000 | 714 | 203 | 8.5 |
| 205R16C-8PR | 110/106S | 6.0J | 5.5J-6.5J | 340 | 1060 | 1000 | 734 | 208 | 8.5 |
| 215/75R16C-8PR | 113/111Q | 6.0J | 5.5J-7J | 450 | 975 | 900 | 728 | 216 | 8.5 |
| 215/75R16LT-8PR | 113/111Q | 6.0J | 5.5J-7J | 450 | 975 | 900 | 728 | 216 | 8.5 |
| 225/65R16C-8PR | 112/110R | 6.5J | 6.0J-7.0J | 475 | 1120 | 1060 | 698 | 228 | 8.5 |

RS903



- Suitable for various mini buses and light goods vehicles. Innovative rubber formulation provides excellent tire wear resistance and reduced rolling resistance.
- Streamline pattern combine with lateral grooves provide excellent water dispersion and a quieter driving experience.

Benefits



Quiet

Vehicle



| Tire Size | LI&GR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|--------------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 145R12LT-6PR | 8078Q | 400B | 350B-4.0J | 350 | 450 | 425 | 537 | 145 | 7.5 |
| 155R12C-6PR | 8381Q | 450B | 400B-5.0J | 350 | 487 | 462 | 553 | 157 | 7.5 |

RS904



- 4 wide grooves design provide effective drainage and sufficient wet safety performance. Multiple blade groove pattern design can provide excellent grip performance and handling performance on wet land.
- The compact shoulder design can provide good handling performance and low noise. Wear-resistant tread formulation promises a longer mileage. Special sidewall structure helps promote the support and durability and further improve handling performance and prolong tires service life. Design of central with sipes promotes the rigidity help to balance high-speed performance and grip performance

Benefits



Longer Mileage



Comfort



Quiet



Economy

Vehicle



| Tire Size | LI&GR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|--------------|-----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 215/75R16 | 100T | 6.0J | 5.5J-6.5J | 300 | 800 | | 703 | 216 | 8.5 |
| 225/75R16 | 102T/105S | 6.0J | 5.5J-6.5J | 350 | 850 | | 719 | 223 | 8.5 |
| 215/70R16 | 100T | 6.5J | 5.5J-7.0J | 350 | 800 | | 708 | 221 | 8.5 |
| 225/70R16 | 103T | 6.5J | 6.0J-7.5J | 340 | 975 | | 722 | 228 | 8.5 |
| 235/60R16 | 100HV | 7.0J | 7.0J-8.5J | 350 | 800 | | 688 | 240 | 8.5 |
| 235/70R16 | 106T | 7.0J | 6.0J-8.0J | 350 | 950 | | 736 | 240 | 8.5 |
| 245/70R16 | 107T | 7.0J | 6.5J-8.0J | 350 | 975 | | 750 | 248 | 8.5 |
| 255/65R16 | 109H | 7.5J | 6.5J-8.0J | 350 | 1030 | | 738 | 260 | 8.5 |
| 255/70R16 | 111T | 7.5J | 7.0J-8.5J | 350 | 1090 | | 764 | 260 | 8.5 |
| 265/70R16 | 112T | 8.0J | 7.5J-9.0J | 350 | 1120 | | 778 | 272 | 8.5 |
| 275/70R16 | 114H/T | 8.0J | 7.5J-9.0J | 350 | 1180 | | 792 | 279 | 8.5 |
| 215/60R17 | 96H | 6.5J | 6.0J-7.5J | 350 | 710 | | 690 | 221 | 8.5 |
| 225/60R17 | 99H | 6.5J | 6.0J-8.0J | 350 | 775 | | 702 | 228 | 8.5 |
| 235/55R17 XL | 103V | 7.5J | 7.0J-8.0J | 350 | 775 | | 690 | 245 | 8.5 |
| 235/65R17 XL | 108H | 7.0J | 7.0J-8.5J | 350 | 900 | | 738 | 240 | 8.5 |
| 245/65R17 XL | 111H | 7.0J | 7.0J-8.5J | 350 | 975 | | 750 | 248 | 8.5 |
| 255/60R17 | 106V | 7.5J | 7.0J-8.0J | 350 | 950 | | 739 | 240 | 8.5 |
| 265/65R17 | 112H | 8.0J | 7.5J-9.0J | 350 | 1120 | | 776 | 272 | 8.5 |
| 265/70R17 | 115T | 8.0J | 7.5J-9.0J | 300 | 1215 | | 804 | 272 | 8.5 |
| 275/65R17 | 115H | 8.0J | 7.5J-9.0J | 350 | 1215 | | 790 | 279 | 8.5 |
| 265/65R17 | 116H | 9.0J | 8.0J-10.0J | 300 | 1250 | | 803 | 285 | 8.5 |
| 235/55R18 XL | 104V | 7.5J | 7.0J-8.0J | 350 | 800 | | 715 | 245 | 8.5 |
| 255/55R18 XL | 109V | 8.0J | 7.5J-8.5J | 350 | 925 | | 738 | 265 | 8.5 |
| 265/60R18 | 110H | 8.0J | 7.5J-8.5J | 340 | 1060 | | 775 | 272 | 8.5 |
| 275/65R18 | 116H | 8.0J | 7.5J-9.5J | 300 | 1250 | | 815 | 279 | 8.5 |
| 285/50R20 XL | 116V | 9.0J | 8.5J-9.5J | 300 | 1120 | | 794 | 297 | 8.5 |

RS905



- Reinforced carcass design and tread compound formula provide tire with excellent wear resistance performance.
- Rigid and straight pattern blocks provide tire with excellent driving performance, grip performance and safety handling performance. Pattern with different pitches can effectively reduce the noise during traveling and provide comfortable ride.
- Optimized pattern groove depth provides you with longer mileage.

Benefits



Comfort



Longer Mileage

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|----------------|---------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 6.00R13LT-10PR | 9893L | 4.50B | 4.50B | 560 | 750 | 670 | 655 | 170 | 11.0 |
| 6.00R14LT-10PR | 10066L | 4.5J | 4.5J | 560 | 800 | 710 | 680 | 170 | 11.0 |
| 6.00R15LT-10PR | 10597L | 4.5E | 4.5E | 560 | 825 | 730 | 705 | 170 | 11.0 |
| 6.50R15LT-8PR | 10197Q | 5.50F | 6.00G | 460 | 825 | 730 | 730 | 185 | 8.5 |
| 7.00R15LT-10PR | 109106Q | 5.50F | 6.00G | 560 | 1030 | 925 | 750 | 200 | 9.5 |
| 6.50R16LT-10PR | 107102Q | 5.50F | 5.00E | 560 | 500F | 850 | 750 | 185 | 8.5 |
| 7.00R16LT-10PR | 111107Q | 5.50F | 6.00G | 560 | 1100 | 965 | 775 | 200 | 9.5 |

RS906



- Suitable for various premium saloon cars.
- The innovative central rib design provides excellent steering and grip ability on wet road surface.
- Balance of mileage and oil efficiency performance.
- Perfect economy and Environmental friendly.

Benefits



Comfort



Longer Mileage



Quiet

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-----------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 155/70R13 | 75T | 4.50B | 4.00B-5.00B | 250 | 387 | | 548 | 157 | 7.6 |
| 165/65R13 | 77T | 5.0J | 4.5J-6.0J | 300 | 412 | | 544 | 170 | 7.6 |
| 165/70R13 | 79T | 5.0J | 4.0J-5.5J | 300 | 437 | | 562 | 170 | 7.6 |
| 175/60R13 | 77H | 5.0J | 5.0J-6.0J | 300 | 412 | | 540 | 177 | 7.6 |
| 175/70R13 | 82T | 5.0J | 4.5J-6.0J | 300 | 475 | | 576 | 177 | 7.6 |
| 185/60R14 | 75H | 5.0J | 4.5J-6.0J | 300 | 387 | | 554 | 170 | 7.6 |
| 185/60R14 | 82T | 5.5J | 5.0J-6.5J | 300 | 475 | | 578 | 189 | 7.6 |
| 185/65R14 | 86H | 5.5J | 5.0J-6.5J | 300 | 530 | | 596 | 189 | 7.6 |
| 185/70R14 | 88H | 5.5J | 4.5J-6.0J | 300 | 560 | | 616 | 189 | 7.6 |
| 195/60R14 | 86H | 6.0J | 5.5J-7.0J | 300 | 530 | | 590 | 201 | 7.6 |
| 195/70R14 | 91H | 6.0J | 5.0J-6.5J | 300 | 615 | | 630 | 201 | 7.6 |
| 205/60R14 | 88H | 5.5J | 5.5J-7.5J | 300 | 560 | | 602 | 209 | 7.6 |
| 205/70R14 | 95T | 6.0J | 5.5J-6.5J | 300 | 690 | | 644 | 209 | 7.6 |
| 185/65R15 | 88H | 5.5J | 5.0J-6.5J | 350 | 560 | | 621 | 189 | 7.6 |
| 195/60R15 | 88H | 6.0J | 5.5J-7.0J | 300 | 560 | | 615 | 201 | 7.6 |
| 195/65R15 | 91H | 6.0J | 5.5J-7.0J | 300 | 560 | | 615 | 201 | 7.6 |
| 205/60R15 | 91H | 6.0J | 5.5J-7.5J | 300 | 615 | | 627 | 209 | 7.6 |
| 205/65R15 | 94H | 6.0J | 5.5J-7.5J | 300 | 670 | | 647 | 209 | 7.6 |

RS907



- Suitable for various sub-compact and family saloon cars. 3 longitudinal wide grooves provides excellent water dispersion and skid resistance.
- Lateral streamline grooves combine with sipes provide excellent grip and braking ability.
- 2 central longitudinal grooves provides excellent tire wear resistance and

Benefits



Comfort



Quiet

Vehicle



| Tire Size | LI&DR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-----------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 145/70R12 | 68S | 4.50B | 4.00B-5.00B | 250 | 325 | | 509 | 150 | 7.5 |
| 165/75R13 | 81S | 4.50B | 4.00B-5.00B | 250 | 462 | | 578 | 165 | 7.5 |
| 185/70R13 | 86T | 5.50B | 5.00B-6.00B | 250 | 530 | | 590 | 189 | 7.5 |
| 185/70R14 | 88H | 5.5J | 5.0J-6.0J | 250 | 560 | | 618 | 189 | 7.5 |

RS908



- Suitable for various commercial vehicles and family saloon cars. Longitudinal main groove design provides high speed driving stability.
- Zigzag lateral sipes provides powerful traction and grip ability uniform tread wear for a longer tire life.

Benefits



Longer Mileage



Powerful Traction

Vehicle



| Tire Size | LI&DR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|--------------------------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 175/75R14 | 80H | 5.0J | 4.5J-5.5J | 250 | 530 | | 618 | 177 | 7.5 |
| 175/80R14 | 88S | 5.0J | 4.5J-5.5J | 240 | 560 | | 636 | 177 | 7.5 |
| 185/75R14 | 80H | 5.0J | 4.5J-5.5J | 250 | 580 | | 634 | 184 | 7.5 |
| 195/75R14 | 92H | 5.5J | 5.0J-6.0J | 250 | 630 | | 648 | 196 | 7.5 |
| LT215/75R15-8PR 108/103Q | | 6.0J | 5.5J-6.5J | 450 | 950 | 875 | 703 | 216 | 8.5 |
| LT235/75R15-8PR 110/107Q | | 6.5J | 6.0J-7.0J | 450 | 1080 | 975 | 733 | 235 | 11.0 |

RS909



- Suitable for various premium saloon and sports cars.
- Unique U-shaped unidirectional pattern design provides uniform pressure distribution, excellent cornering grip ability and uneven tire wear resistance.
- Adopting an extra-wide center rib to increase vehicles steering reliability and response. Adopts an optimized 5-pitch tread design and a multi-sipe arrangement both on the shoulder and center rib, which effectively reduces tire noise during travel.
- 4 wide circumferential grooves provide excellent water dispersion and driving stability on slippery

Benefits

Vehicle



Comfort



Quiet



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|--------------|---------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 195/45R15 | 78V | 6.5J | 6.0J-7.5J | 300 | 425 | | 557 | 195 | 7.7 |
| 205/50R15 | 86H | 6.5J | 5.5J-7.5J | 350 | 530 | | 587 | 214 | 7.7 |
| 205/55R15 | 88V | 6.5J | 5.5J-7.5J | 350 | 580 | | 607 | 214 | 7.7 |
| 205/60R15 | 91V | 6.0J | 5.5J-7.5J | 300 | 615 | | 627 | 209 | 7.7 |
| 195/45R16 | 80V | 6.5J | 6.0J-7.5J | 300 | 450 | | 582 | 195 | 7.7 |
| 205/45R16 | 87W | 7.0J | 6.5J-7.5J | 340 | 545 | | 590 | 206 | 7.7 |
| 205/50R16 XL | 91W | 6.5J | 5.5J-7.5J | 340 | 615 | | 612 | 214 | 7.7 |
| 205/55R16 XL | 94V | 6.5J | 5.5J-7.5J | 340 | 670 | | 632 | 214 | 7.7 |
| 205/60R16 | 92V | 6.0J | 5.5J-7.5J | 300 | 630 | | 652 | 209 | 7.7 |
| 215/55R16 XL | 97V | 7.0J | 6.0J-7.5J | 340 | 730 | | 642 | 228 | 7.7 |
| 215/60R16 | 95V | 6.5J | 6.0J-7.5J | 300 | 680 | | 664 | 221 | 7.7 |
| 225/55R16 XL | 99W | 7.0J | 6.0J-8.0J | 350 | 775 | | 654 | 233 | 7.7 |
| 225/60R16 | 98V | 6.5J | 6.0J-8.0J | 300 | 750 | | 676 | 228 | 7.7 |
| 205/40R17 XL | 84W | 7.5J | 7.0J-8.0J | 340 | 500 | | 596 | 212 | 7.7 |
| 205/50R17 XL | 93W | 6.5J | 5.5J-7.5J | 350 | 650 | | 638 | 214 | 7.7 |
| 215/45R17 XL | 91Y | 7.0J | 7.0J-8.0J | 340 | 615 | | 626 | 213 | 7.7 |
| 215/50R17 | 91V/95W | 7J | 6.0J-7.5J | 350 | 615 | | 648 | 228 | 7.7 |
| 215/55R17 | 94V | 7.0J | 6.0J-7.5J | 300 | 670 | | 668 | 228 | 7.7 |
| 225/45R17 XL | 94W | 7.5J | 7.0J-8.5J | 340 | 670 | | 634 | 225 | 7.7 |
| 225/50R17 XL | 98W | 7.0J | 6.0J-8.0J | 350 | 750 | | 658 | 233 | 7.7 |
| 235/45R17 XL | 97Y | 8.0J | 7.5J-9.0J | 340 | 730 | | 644 | 236 | 7.7 |
| 235/50R17 | 96W | 7.5J | 6.5J-8.5J | 350 | 710 | | 668 | 245 | 7.7 |
| 225/40R18 XL | 92Y | 8.0J | 7.5J-9.0J | 340 | 630 | | 637 | 230 | 7.7 |

RS910



- Suitable for various premium saloon cars. The innovative central rib design provides excellent steering and grip ability on wet road surface.
- Wider pattern block design on shoulder extremely improved uniform tire wear performance. Adopts an optimized 5-pitch tread design which effectively reduces tire noise during travel.
- Dispersion and driving stability on slippery surface.

Benefits

Vehicle



Comfort



Quiet



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|--------------|---------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 195/55R15 | 89V | 6.0J | 5.5J-7.0J | 300 | 515 | | 595 | 201 | 7.5 |
| 215/65R15 XL | 100H | 6.5J | 6.0J-7.5J | 340 | 800 | | 661 | 221 | 7.5 |
| 215/70R15 | 98T/98H | 6.5J | 5.5J-7.0J | 350 | 750 | | 683 | 221 | 8.2 |
| 195/60R16 | 89H | 6.0J | 5.5J-7.0J | 350 | 580 | | 640 | 201 | 7.6 |
| 205/65R16 | 95H | 6.0J | 5.5J-7.0J | 350 | 680 | | 672 | 209 | 7.6 |
| 195/55R16 | 87V | 6.0J | 5.5J-7.0J | 300 | 545 | | 620 | 201 | 8.0 |
| 205/55R16 | 91V | 6.5J | 5.5J-7.5J | 300 | 615 | | 632 | 214 | 7.5 |
| 205/50R16 XL | 91W | 6.5J | 5.5J-7.5J | 340 | 615 | | 612 | 214 | 7.5 |

RS915



- Suitable for various light pickup trucks and mid-sized buses. Block pattern with sipes effectively removes water layer on road surface; providing excellent traction and grip ability.
- Innovative pattern design provides good self-cleaning ability and is suitable for all kinds of road surface especially in mud and snow condition. Provides a safer driving experience. Good tire wear resistance; Suitable for high-speed driving on both city and country-side roads.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-------------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 31x10.50R15LT-6PR | 109Q | 8.5J | 8.0J-9.0J | 350 | 1030 | | 775 | 268 | 12.5 |
| LT215/75R15-8PR | 106/103Q | 6.0J | 5.5J-6.5J | 450 | 950 | 875 | 703 | 216 | 8.5 |
| LT235/75R15-8PR | 110/107Q | 6.5J | 6.0J-7.0J | 450 | 1060 | 975 | 733 | 235 | 11.0 |
| 21580R16C-8PR XL | 107S | 6.0J | 5.5J-6.5J | 290 | 975 | | 750 | 216 | 9.5 |
| LT235/85R16-10PR | 120/116Q | 6.5J | 6.0J-7.0J | 550 | 1400 | 1250 | 806 | 235 | 11.5 |

RS916



- Provide outstanding performance in both on-road and off road driving applications. The pattern exploits a combination of features specially suited to provide solid all-terrain performance.
- Superior all-season traction, excellent stability, confident handling and reliable tread wear.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|------------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 205/70R15 | 96H | 6.0J | 5.0J-7.0J | 300 | 710 | | 669 | 209 | 8.4 |
| 215/75R15 | 100T | 6.0J | 5.5J-7.0J | 300 | 800 | | 703 | 216 | 8.4 |
| 235/75R15 XL | 109T | 6.5J | 6.0J-8.0J | 300 | 1030 | | 733 | 235 | 8.7 |
| 215/70R16 | 100H | 6.5J | 5.5J-7.0J | 300 | 800 | | 708 | 221 | 8.4 |
| 225/70R16 | 103T | 6.5J | 6.0J-7.5J | 300 | 875 | | 722 | 228 | 11.4 |
| 235/70R16 | 106T | 7.0J | 6.0J-8.0J | 300 | 950 | | 736 | 240 | 8.4 |
| 245/70R16 XL | 111S | 7.0J | 6.5J-8.0J | 340 | 1090 | | 750 | 248 | 8.4 |
| 245/75R16 | 111T | 7.0J | 6.5J-8.0J | 300 | 1090 | | 774 | 248 | 8.4 |
| 265/70R16 | 112T | 8.0J | 7.0J-9.0J | 300 | 1120 | | 778 | 272 | 8.4 |
| 265/75R16 | 116S | 7.5J | 7.0J-9.0J | 300 | 1250 | | 804 | 267 | 8.4 |
| 275/70R16 | 114H | 8.0J | 7.5J-9.5J | 300 | 1180 | | 792 | 279 | 8.8 |
| 235/60R17 | 102H | 7.0J | 6.5J-8.5J | 300 | 850 | | 714 | 240 | 8.4 |
| 235/65R17 XL | 108T | 7.0J | 6.5J-8.5J | 340 | 1000 | | 738 | 240 | 11.5 |
| 265/65R17 | 112H | 8.0J | 7.5J-9.5J | 300 | 1120 | | 776 | 272 | 8.4 |
| 275/65R17 | 115T | 8.0J | 7.5J-9.5J | 300 | 1215 | | 790 | 279 | 8.4 |
| 235/85R16LT-10PR | 120/116S | 6.5J | 6.0J-7.5J | 550 | 1400 | | 806 | 235 | 8.5 |

RS917



- Block pattern with sipes effectively removes water layer on road surface; providing excellent traction and grip ability.
- Innovative pattern design provides good self-cleaning ability and is suitable for all kinds of road surface especially in mud and snow condition. Provides a safer driving experience.

Benefits



Comfort



Economy

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-----------------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 265/65R17 XL | 112T | 8.0J | 7.5J-8.5J | 300 | 1120 | | 778 | 272 | 8.7 |
| White side wall | | | | | | | | | |
| 265/65R17 XL | 112T | 8.0J | 7.5J-8.5J | 300 | 1120 | | 778 | 272 | 8.7 |

RS919



- Increased tire-to-road contact leads to improvements in tread wear and handling. Solid center rib along with a refined tread element shape helps provide even tread wear.
- Shoulder slotting is designed for resistance to irregular wear while providing solid all-season performance.

Benefits



Comfort




Powerful Traction



Mixed Surface

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|--------------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 215/65R16 | 98H | 6.5J | 6.0J-7.0J | 300 | 750 | | 686 | 221 | 9.5 |
| 215/60R17 | 96H | 6.5J | 6.0J-7.5J | 350 | 710 | | 690 | 221 | 8.5 |
| 225/65R17 XL | 101H | 7.0J | 6.5J-7.5J | 340 | 825 | | 680 | 233 | 8.2 |
| 225/60R17 | 99H | 6.5J | 6.0J-7.0J | 300 | 775 | | 702 | 228 | 9.5 |

RS920



- 4 longitudinal grooves provides excellent linear driving ability. Variable pitch groove design reduces tire noise during driving.
- Block pattern combined with lateral sipes ensure excellent grip ability, water dispersion and skid resistance.

Benefits



Quiet



Economy



Comfort

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|--------------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 21555R16 | 93W | 7.0J | 6.5J-7.5J | 300 | 650 | | 642 | 228 | 8.2 |
| 22570R16 | 103T | 6.5J | 6.0J-7.5J | 300 | 875 | | 722 | 228 | 11.4 |
| 23560R16 | 100T | 7.0J | 6.5J-7.5J | 300 | 800 | | 698 | 240 | 8.5 |
| 23570R16 | 106T | 7.0J | 6.0J-8.0J | 300 | 950 | | 736 | 240 | 8.4 |
| 24570R16 XL | 111S | 7.0J | 6.5J-8.0J | 340 | 980 | | 750 | 248 | 8.4 |
| 22555ZR17 XL | 101W | 7.0J | 6.5J-7.5J | 340 | 825 | | 690 | 233 | 8.2 |
| 22565R17 | 102T | 6.5J | 6.0J-7.0J | 300 | 850 | | 724 | 228 | 9.2 |
| 23560R17 | 102H | 7.0J | 6.5J-8.5J | 300 | 850 | | 714 | 240 | 8.4 |
| 23565R17 XL | 108T | 7.0J | 6.5J-8.5J | 340 | 1000 | | 738 | 240 | 11.4 |
| 24545ZR17 XL | 95 YW | 8.0J | 7.5J-9.5J | 300 | 690 | | 243 | 652 | 8.4 |
| 26565R17 | 112H | 8.0J | 7.5J-9.5J | 300 | 1120 | | 776 | 272 | 8.4 |
| 21536ZR18 XL | 84Y | 7.5J | 6.5J-8.0J | 290 | 500 | | 607 | 218 | 8.3 |
| 22545ZR18 XL | 95W | 7.5J | 6.5J-8.0J | 290 | 690 | | 659 | 225 | 8.2 |
| 23540ZR18 XL | 95W | 8.5J | 7.5J-9.5J | 350 | 690 | | 637 | 230 | 7.8 |
| 23560R18 XL | 107V | 7.0J | 6.5J-8.5J | 340 | 975 | | 739 | 240 | 8.2 |
| 24540ZR18 XL | 97 YW | 8.5J | 7.5J-9.5J | 350 | 730 | | 653 | 248 | 8.2 |
| 24545ZR18 | 100W | 8.0J | 7.0J-9.0J | 350 | 710 | | 677 | 243 | 7.8 |
| 25545ZR18 | 99W | 8.5J | 8.0J-9.5J | 300 | 775 | | 687 | 255 | 7.8 |
| 25555R18 XL | 109V | 8.0J | 7.0J-9.0J | 340 | 1030 | | 737 | 265 | 8.2 |
| 25560R18 XL | 112V | 7.5J | 7.0J-9.0J | 340 | 1120 | | 763 | 260 | 8.2 |
| 26560R18 | 110V | 8.0J | 7.5J-9.5J | 350 | 1030 | | 737 | 265 | 9.0 |
| 25550R19 XL | 107V | 8.0J | 7.0J-9.0J | 340 | 975 | | 739 | 265 | 8.2 |
| 28545R19 XL | 111V | 9.5J | 9.0J-10.5J | 340 | 1090 | | 739 | 285 | 8.2 |
| 27540R20 XL | 106V | 9.5J | 9.0J-11.0J | 340 | 950 | | 728 | 278 | 8.2 |

RS921



- Suitable for various commercial vehicles.
- 4 main tread grooves provides excellent straight running stability. Variable pitch groove design reduces tire noise while on the road.

Benefits



Quiet



Economy



Powerful Traction

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-----------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 22570R16 | 103T | 6.5J | 6.0J-7.0J | 250 | 875 | | 722 | 228 | 8.5 |

RS922



- Large-block design, large contact surface and optimized tread contact patch to improve dry handling performance.
- Four main central grooves, maximize water drainage for good aquaplaning & wet grip performance.
- Asymmetric design with optimized pitch sequence, smoother impact groove resonance reduction for new and worn tire noise.

Benefits



Comfort



Longer Mileage

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|---------------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 215/55R16 XL | 97W | 7.0J | 6.0J-7.5J | 340 | 730 | | 642 | 226 | 7.8 |
| 225/55R17 XL | 101W | 7.0J | 6.0J-7.0J | 350 | 730 | 825 | 680 | 233 | 7.8 |
| 245/45R17 | 99W | 8.0J | 7.0J-9.0J | 350 | 690 | 775 | 652 | 243 | 7.8 |
| 215/35ZR18 XL | 84W | 7.5J | 7.0J-8.5J | 350 | 500 | | 607 | 218 | 7.8 |
| 225/45ZR18 | 91W | 7.5J | 7.0J-8.5J | 350 | 615 | | 659 | 225 | 7.8 |
| 235/40RR18 | 95W | 8.5J | 8.0J-9.0J | 340 | 690 | | 645 | 241 | 7.8 |
| 245/40ZR18 XL | 97W | 8.5J | 8.0J-9.5J | 340 | 730 | | 653 | 248 | 7.7 |
| 245/45ZR18 XL | 100W | 8.0J | 7.5J-9.0J | 340 | 800 | | 677 | 243 | 7.7 |
| 255/45ZR18 XL | 103Y | 8.5J | 8.0J-9.5J | 340 | 875 | | 687 | 255 | 7.7 |
| 265/35ZR18 XL | 97Y | 9.5J | 9.0J-10.5J | 350 | 730 | | 643 | 271 | 7.8 |
| 235/35ZR19 XL | 91W | 8.5J | 8.0J-9.5J | 350 | 545 | 615 | 647 | 241 | 7.8 |
| 245/35ZR19 XL | 93W | 8.5J | 8.0J-9.5J | 350 | 580 | 650 | 655 | 248 | 7.8 |
| 245/40ZR19 XL | 98Y | 8.5J | 8.0J-9.5J | 350 | 670 | 750 | 679 | 248 | 7.7 |
| 245/35ZR20 | 95Y | 8.5J | 8.0J-9.5J | 350 | 615 | 690 | 680 | 248 | 7.8 |
| 255/35ZR20 XL | 97Y | 9.0J | 8.5J-10.0J | 350 | 650 | 730 | 696 | 260 | 7.8 |
| 295/35ZR21 XL | 107Y | 10.5J | 10.0J-11.5J | 340 | 975 | | | | 8.1 |
| 265/35ZR22 XL | 102Y | 9.5J | 9.0J-10.5J | 340 | 850 | | 745 | 271 | 6.7 |

RS924



- Suitable for various mid-sized vans, light trucks and buses. Longitudinal zigzag grooves combine with sipes provides excellent grip ability, water dispersion and skid resistance.
- Unique longitudinal tread blocks pattern combine with special rubber formulation provide enhanced tire wear resistance and driving comfort.

Benefits




Comfort



Longer Mileage

Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 205R14C-6PR | 105/103Q | 6.0J | 5.5J-6.5J | 375 | 925 | 875 | 684 | 208 | 8.0 |

RS925



- Suitable for various light trucks and buses / pickup trucks etc. Excellent water dispersion and skid resistance.
- Ribbed block ensures better steering response and driving stability. Variable pitch groove design provides a quieter ride.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|----------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 215/70R15C-8PR | 109/107Q | 6.5J | 5.5J-7.0J | 450 | 1030 | 975 | 683 | 221 | 8.0 |

RS926



- Suitable for various minibuses / light trucks and buses / pickup trucks etc. Variable pitch groove design reduces tire noise during high speed driving.
- Optimized profile design provides uniform tire wear and longer tire life. Longitudinal main grooves combine with lateral sipes and zigzag sipes ensure excellent road adhesion.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|----------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 225/70R15C-8PR | 112/110Q | 6.5J | 6.0J-7.0J | 450 | 1120 | 1060 | 697 | 228 | 8.5 |

RS928



- Suitable for mid-level to premium cars.
High buffering base compound increase comfort and reduce noise.
- Four groove and high density siping design improve wet grip.
Balance of mileage and oil efficiency performance.
Perfect economy and Environmental friendly.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-----------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 155/70R12 | 73T | 4.50B | 4.00B-5.00B | 300 | 365 | | 523 | 157 | 7.6 |
| 175/70R12 | 80H | 5.00B | 4.50B-5.00B | 300 | 450 | | 551 | 177 | 7.6 |
| 155/85R13 | 73T | 4.50J | 4.5J-5.5J | 300 | 365 | | 532 | 157 | 7.6 |
| 155/70R13 | 75T | 4.50B | 4.5J-5.00B | 300 | 387 | | 548 | 157 | 7.6 |
| 155/80R13 | 79T | 4.50B | 4.5J-5.00B | 300 | 437 | | 578 | 157 | 7.6 |
| 165/85R13 | 77T | 5.0J | 4.5J-6.0J | 300 | 412 | | 544 | 170 | 7.6 |
| 165/70R13 | 79H | 5.00B | 5.0J-5.00B | 300 | 437 | | 562 | 170 | 7.6 |
| 165/80R13 | 83T | 4.50B | 4.5J-5.00B | 300 | 487 | | 594 | 185 | 7.6 |
| 175/80R13 | 77H | 5.0J | 5.0J-6.0J | 300 | 412 | | 540 | 177 | 7.6 |
| 175/85R13 | 80T | 5.0J | 5.0J-6.0J | 300 | 450 | | 558 | 177 | 7.6 |
| 175/70R13 | 82T | 5.0J | 4.5J-6.0J | 300 | 475 | | 576 | 177 | 7.6 |
| 165/70R13 | 86T | 5.5J | 4.5J-6.0J | 300 | 530 | | 590 | 189 | 7.6 |
| 155/85R14 | 75T | 4.5J | 4.5J-5.5J | 300 | 365 | | 532 | 157 | 7.6 |
| 165/80R14 | 75H | 5.0J | 4.5J-6.0J | 300 | 387 | | 554 | 170 | 7.6 |
| 165/85R14 | 79H | 5.0J | 4.5J-6.0J | 300 | 437 | | 570 | 170 | 7.6 |
| 165/70R14 | 81T | 5.0J | 4.0J-5.5J | 300 | 462 | | 588 | 170 | 7.6 |
| 175/85R14 | 82T | 5.0J | 5.0J-6.0J | 300 | 475 | | 584 | 177 | 7.6 |
| 175/70R14 | 84T | 5.0J | 4.5J-6.0J | 300 | 500 | | 602 | 177 | 7.6 |
| 185/55R14 | 80H | 6.0J | 5.0J-6.5J | 300 | 450 | | 590 | 194 | 7.6 |
| 185/80R14 | 82T | 5.5J | 5.0J-6.5J | 300 | 475 | | 578 | 189 | 7.6 |
| 185/85R14 | 88H | 5.5J | 5.0J-6.5J | 300 | 530 | | 596 | 189 | 7.6 |
| 165/70R14 | 88H | 5.5J | 4.5J-6.0J | 300 | 580 | | 616 | 189 | 7.6 |

RS928



- Suitable for mid-level to premium cars.
High buffering base compound increase comfort and reduce noise.
- Four groove and high density siping design improve wet grip.
Balance of mileage and oil efficiency performance.
Perfect economy and Environmental friendly.

Benefits



Vehicle




| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|--------------|---------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 185/80R14 | 91T | 5.0J | 4.5J-5.5J | 300 | 615 | | 652 | 184 | 7.6 |
| 195/80R14 | 88H | 6.0J | 5.5J-7.0J | 300 | 530 | | 590 | 201 | 7.6 |
| 195/70R14 | 91H | 6.0J | 5.0J-6.5J | 300 | 615 | | 630 | 201 | 7.6 |
| 205/70R14 | 95T | 6.0J | 5.5J-6.5J | 300 | 690 | | 644 | 209 | 7.6 |
| 175/85R15 | 84H | 5.0J | 5.0J-5.5J | 300 | 500 | | 609 | 177 | 7.6 |
| 185/55R15 | 82H | 6.0J | 5.0J-6.5J | 300 | 475 | | 585 | 194 | 7.6 |
| 185/80R15 | 84H | 5.5J | 5.0J-6.5J | 300 | 500 | | 603 | 189 | 7.6 |
| 185/85R15 | 88H | 5.5J | 5.0J-6.5J | 350 | 580 | | 621 | 189 | 7.6 |
| 195/50R15 | 82H | 6.0J | 5.5J-6.5J | 300 | 475 | | 577 | 201 | 7.6 |
| 195/55R15 | 85H | 6.0J | 5.5J-7.0J | 300 | 515 | | 595 | 201 | 7.6 |
| 195/60R15 | 88H | 6.0J | 5.5J-7.0J | 300 | 580 | | 615 | 201 | 7.6 |
| 195/65R15 | 91H | 6.0J | 5.5J-7.0J | 300 | 615 | | 635 | 201 | 7.6 |
| 205/60R15 | 91H | 6.0J | 5.5J-7.5J | 300 | 615 | | 627 | 209 | 7.6 |
| 205/65R15 | 94H | 6.0J | 5.5J-7.5J | 300 | 670 | | 647 | 209 | 7.6 |
| 205/70R15 | 96H | 6.0J | 5.5J-7.0J | 300 | 710 | | 669 | 209 | 7.6 |
| 215/70R15 | 98H | 6.5J | 5.5J-7.0J | 300 | 750 | | 683 | 221 | 8.2 |
| 195/55R16 | 87H/87V | 6.0J | 5.5J-7.5J | 300 | 615 | | 632 | 201 | 7.6 |
| 205/50R16 | 87H/91V | 6.5J | 5.5J-7.5J | 350/340 | 615 | | 612 | 214 | 7.6 |
| 205/55R16 | 91H | 6.5J | 5.5J-7.5J | 300 | 615 | | 632 | 214 | 7.6 |
| 215/65R16 | 96H | 6.5J | 6.0J-7.0J | 350 | 750 | | 686 | 221 | 7.6 |
| 225/50ZR16 | 87W | 6.5J | 6.0J-8.0J | 300 | 630 | | 632 | 233 | 7.6 |
| 225/55R16 XL | 96W | 7.0J | 6.0J-8.0J | 340 | 775 | | 654 | 233 | 7.6 |

RS929



- Willow leaf-shaped biomimetic tread block design. Adopting willow-shaped biomimetic pattern block design inside, effectively prevent abnormal wear of pattern block corners. Together with "S" shaped on tread grooves, bring soft silence and comfort. Asymmetric design.
- 4 wide grooves design provide effective drainage and sufficient wet safety performance.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|---------------|-------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 205/45ZR16 XL | 87W | 7.0J | 6.5J-7.5J | 340 | 545 | | 590 | 208 | 8.5 |
| 205/40ZR17 XL | 84W | 7.5J | 7.0J-8.0J | 340 | 500 | | 596 | 212 | 8.5 |
| 205/45ZR17 XL | 88W | 7.0J | 6.0J-7.5J | 340 | 580 | | 616 | 206 | 8.5 |
| 205/50ZR17 XL | 93W | 6.5J | 5.5J-7.5J | 340 | 650 | | 638 | 214 | 8.5 |
| 215/40ZR17 XL | 87W | 7.5J | 7.0J-8.5J | 350 | 487 | | 604 | 218 | 8.5 |
| 215/45ZR17 XL | 91W | 7.0J | 7.0J-8.0J | 340 | 615 | | 630 | 213 | 8.5 |
| 215/50ZR17 XL | 95W | 7.0J | 6.0J-7.5J | 350 | 615 | | 648 | 226 | 8.5 |
| 215/55ZR17 XL | 98W | 7.0J | 6.0J-7.5J | 300 | 670 | | 668 | 228 | 8.5 |
| 225/45ZR17 XL | 94W | 7.5J | 7.0J-8.5J | 340 | 670 | | 634 | 225 | 8.5 |
| 225/50ZR17 XL | 98W | 7.0J | 6.0J-8.0J | 340 | 750 | | 658 | 233 | 8.5 |
| 225/55ZR17 XL | 101W | 7.0J | 6.0J-8.0J | 340 | 825 | | 680 | 233 | 8.5 |
| 235/45ZR17 XL | 97W | 8.0J | 7.5J-9.0J | 350 | 670 | | 644 | 236 | 8.5 |
| 235/55ZR17 XL | 103W | 7.5J | 6.5J-8.5J | 340 | 875 | | 690 | 245 | 8.5 |
| 245/45ZR17 XL | 99W | 7.5J | 7.0J-8.5J | 350 | 600 | | 634 | 225 | 8.5 |
| 215/35ZR18 XL | 84W | 7.5J | 7.5J-9.0J | 340 | 500 | | 607 | 218 | 8.5 |
| 225/40ZR18 XL | 92W | 8.0J | 7.5J-9.0J | 350 | 630 | | 638 | 231 | 8.5 |
| 225/45ZR18 XL | 95W | 7.5J | 7.0J-8.5J | 340 | 690 | | 659 | 225 | 8.5 |
| 235/40ZR18 XL | 95W | 8.5J | 8.0J-9.5J | 350 | 690 | | 645 | 241 | 8.5 |
| 235/45ZR18 XL | 98W | 8.0J | 7.5J-9.0J | 350 | 670 | | 669 | 236 | 8.5 |
| 235/50ZR18 XL | 101W | 7.5J | 6.5J-8.5J | 340 | 825 | | 693 | 245 | 8.5 |
| 225/35ZR19 XL | 88W | 8.5J | 8.0J-9.5J | 340 | 560 | | 641 | 230 | 8.5 |
| 245/45ZR19 XL | 102W | 8.0J | 7.5J-9.5J | 340 | 850 | | 703 | 243 | 8.5 |
| 225/35ZR20 XL | 90W | 8.0J | 7.5J-9.5J | 340 | 650 | | 671 | 229 | 8.5 |
| 235/35ZR20 XL | 92W | 8.5J | 8.0J-9.5J | 340 | 630 | | 672 | 235 | 8.5 |
| 245/35ZR20 XL | 95Y | 8.5J | 8.0J-9.5J | 340 | 690 | | 680 | 248 | 8.5 |
| 255/35ZR20 XL | 97W | 9.0J | 8.5J-10.0J | 350 | 650 | | 685 | 260 | 8.5 |
| 265/50R20 XL | 111V | 8.5J | 8.0J-9.5J | 340 | 1090 | | 774 | 277 | 8.5 |
| 275/40ZR20 XL | 108W | 9.5J | 9.0J-10.0J | 350 | 950 | | 728 | 278 | 8.5 |

RS932



- Multi-sipe design, improved grip on snow and icy roads, to guarantee its handling and braking performance.
- Block tread pattern design, high cross density, improved performance.
- 3D shoulder profile, improved traction and braking performance for rough application. Curved main groove design, increased tread rigidity, to avoid irregular wear under high load operation.
- Low sea-land ratio(Non-saturated) tread design, to guarantee load capability.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|----------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 185/75R16C-8PR | 104/102Q | 5.0J | 4.5J-5.5J | 475 | 900 | 850 | 684 | 184 | 9.5 |

RS933



- 2 wide grooves provide effective drainage and sufficient wet safety performance. Special more sipes and grooves design ensures the block rigidity and enhances the wet grip performance.
- Heat dissipation shoulder design prolongs tire life. Central rib design ensures straight-line driving stability.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|-------------------|-----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 235/70R16 | 106T | 7.0J | 6.0J-8.0J | 300 | 950 | | 736 | 240 | 9.0 |
| 265/70R17 | 115T | 7.0J | 6.5J-8.0J | 350 | 975 | | 750 | 248 | 9.0 |
| 31X10.50R15LT-6PR | 109RS | 8.5J | 8.0J-9.0J | 350 | 1030 | | 775 | 268 | 11.5 |
| LT215/85R16-10PR | 115/12QR | 6.0J | 5.5J-6.5J | 550 | 1215 | 1120 | 772 | 216 | 11.5 |
| LT225/75R16-10PR | 115/12QR | 6.0J | 6.0J-6.5J | 575 | 1450 | 1400 | 744 | 223 | 11.5 |
| LT235/85R16-10PR | 120/118RQ | 6.5J | 6.0J-7.0J | 550 | 1380 | 1260 | 806 | 235 | 11.5 |
| LT245/75R16-10PR | 120/118RQ | 7.0J | 6.5J-7.5J | 550 | 1380 | 1260 | 774 | 248 | 11.5 |
| LT265/70R16-10PR | 121/118Q | 8.0J | 7.5J-8.0J | 450 | 1285 | 1180 | 778 | 272 | 11.5 |
| LT265/75R16-10PR | 123/12R | 7.5J | 7.0J-8.0J | 550 | 1550 | 1440 | 804 | 267 | 11.5 |
| LT285/75R16-10PR | 126/123QR | 8.0J | 7.5J-8.5J | 550 | 1700 | 1550 | 834 | 286 | 11.5 |
| LT235/80R17-10PR | 120/117QR | 6.5J | 6.0J-7.0J | 550 | 1400 | 1285 | 808 | 235 | 11.5 |
| LT245/70R17-10PR | 119/116RS | 7.0J | 6.5J-8.0J | 550 | 1360 | 1250 | 776 | 248 | 11.5 |
| LT245/75R17-10PR | 121/116QR | 7.0J | 6.5J-7.5J | 550 | 1450 | 1320 | 800 | 248 | 11.5 |
| LT265/70R17-10PR | 121/116RS | 8.0J | 7.5J-8.0J | 550 | 1550 | 1400 | 804 | 267 | 11.5 |
| LT265/70R17-8PR | 121/118RS | 8.5J | 8.0J-9.0J | 550 | 1450 | 1320 | 832 | 292 | 11.5 |
| LT265/70R18-10PR | 124/121RS | 8.0J | 7.0J-9.0J | 350 | 1600 | 1450 | 828 | 283 | 11.5 |

RS936



- 3 longitudinal grooves enhance water evacuation. Special more sipes and grooves design enhances the wet grip performance.
- Silent groove design decreases noise while tire rolling effectively. Enhanced shoulder design increases driving stability with high load.

Benefits



Vehicle



| Tire Size | LI&SR | Measure Rim | Alternative Rim | Pressure (KPa) | Single Load(Kg) | Dual Load(Kg) | OD(mm) | SW(mm) | Tread Depth(mm) |
|----------------|----------|-------------|-----------------|----------------|-----------------|---------------|--------|--------|-----------------|
| 195/70R15C-8PR | 104/102S | 6.0J | 5.5J-6.5J | 450 | 900 | 850 | 655 | 201 | 8.5 |
| 205/70R15C-8PR | 106/104S | 6.0J | 5.5J-6.5J | 450 | 950 | 900 | 669 | 209 | 8.5 |
| 215/70R15C-8PR | 109/107S | 6.5J | 6.0J-7.0J | 450 | 1030 | 975 | 683 | 221 | 8.5 |
| 225/70R15C-8PR | 112/110S | 6.5J | 6.0J-7.0J | 450 | 1120 | 1060 | 697 | 228 | 8.5 |
| 175/75R16C-6PR | 98/96Q | 5.0J | 4.5J-5.5J | 475 | 825 | 775 | 668 | 177 | 8.5 |
| 195/60R16C-8PR | 99/97T | 6.0J | 5.5J-6.5J | 375 | 775 | 730 | 640 | 201 | 8.5 |
| 195/65R16C-8PR | 104/102T | 6.0J | 5.5J-6.5J | 475 | 900 | 850 | 660 | 201 | 8.5 |
| 195/75R16C-8PR | 107/105S | 5.5 | 5.0J-6.0J | 475 | 975 | 925 | 698 | 196 | 8.5 |
| 205/65R16C-8PR | 107/105T | 6.0J | 5.5J-6.5J | 475 | 975 | 925 | 672 | 209 | 8.5 |
| 205/70R16C-8PR | 110/118R | 6.0J | 5.5J-6.5J | 475 | 975 | 925 | 686 | 209 | 8.5 |
| 215/60R16C-6PR | 108/106T | 6.5J | 6.0J-7.5J | 475 | 1000 | 950 | 664 | 221 | 8.5 |
| 215/65R16C-8PR | 109/107T | 6.5J | 6.0J-7.5J | 475 | 1030 | 975 | 686 | 221 | 8.5 |
| 225/65R16C-8PR | 112/110T | 6.5J | 6.0J-7.0J | 475 | 1120 | 1060 | 698 | 228 | 8.5 |
| 235/65R16C-8PR | 115/113T | 7.0J | 6.5J-7.5J | 450 | 1215 | 1150 | 712 | 240 | 8.5 |