

# TRACMAX

***TBR TIRES***



***ENJOY PREMIUM QUALITY WITH  
TRACMAX TYRES***

***CATALOGUE 2016***






Working in conjunction with tyre manufacturer Shandong Yonsheng Rubber Group LTD., **ASIAN TYRE SOURCING** distributes the TRACMAX brand among the Americas with 100% exclusivity. TRACMAX specialize in designing and supplying all kind of radial tyres, including passenger car tires, SUV tires, light truck tires, truck and bus tires, etc.

Enjoying high popularity in both domestic and international markets, TRACMAX is made and positioned as a high quality level tire brand from China. TRACMAX brand has a wide range of PCR, LTR, A/T, H/T, VAN and TBR tires.

All the patterns are designed according to the latests markets requirements by our R/D team, listening to our customers word wide. All the tires are produced in first class equipments under a strict quality management system to ensure quality stability. Tracmax has passed the following quality certificates: ISO, DOT, ECE, GCC, INMETRO and LATU. As we focus on the environment and sustainability. TRACMAX is built under low-carbon, low-energy, green technology. THIS IS OUR MAIN VALUE.











GRT936

- 1Application: Steer Wheel for long distance, also can be used on Trailer Wheel. Suitable for highway and common road.
- 2Suitable for high speed on good road surfcae application, with excellent anti-wet property and sideslip resistance.
- 3High wear-resitance and radiating performance.



Standard Wheel Permitted Wheel Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/PSI)				
T93601	11R22.5 144/142M	14	14.5	8.25	279	1050	720	-	-	-	-
T93602	11R22.5 146/143M	16	14.5	8.25	279	1050	830	-	-	-	-
T93603	11R24.5 146/143M	14	14.5	8.25	279	1104	720	-	-	-	-
T93604	11R24.5 149/146M	16	14.5	8.25	279	1104	830	-	-	-	-
T93605	295/75R22.5 144/141M	14	14.0	9.00	298	1014	760	-	-	-	-
T93606	295/75R22.5 146/143M	16	14.0	9.00	298	1014	830	-	-	-	-
T93607	285/75R24.5 144/141M	14	14.0	8.25	283	1050	760	-	-	-	-
T93608	285/75R24.5 147/144M	16	14.0	8.25	283	1050	830	-	-	-	-







## GRT906



- ①Application: Drive Wheel, Suitable for highway and common road.
- ②With Super driving performance and braking performance, high wear-resistance and low heat generation.
- ③Powerful gripping ability and wet skid resistance, lower noise.



Standard Wheel   Permitted Wheel   Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section Width (mm)	O.A. Diameter (mm)	Max. Pressure (kpa/PSI)				
T90601	11R22.5 144/142M	14	20.5	8.25	279	1050	720	-	-	-	-
T90602	11R22.5 146/143M	16	20.5	8.25	279	1050	830	-	-	-	-
T90603	11R24.5 146/143M	14	20.5	8.25	279	1104	720	-	-	-	-
T90604	11R24.5 149/146M	16	20.5	8.25	279	1104	830	-	-	-	-
T90605	295/75R22.5 144/141M	14	18.5	9.00	298	1014	760	-	-	-	-
T90606	295/75R22.5 146/143M	16	18.5	9.00	298	1014	830	-	-	-	-
T90607	285/75R24.5 144/141M	14	18.5	8.25	283	1050	760	-	-	-	-
T90608	285/75R24.5 147/144M	16	18.5	8.25	283	1050	830	-	-	-	-



# GRT939



- ① Application: Steer Wheel for long distance, also can be used on Trailer Wheel. Suitable for highway and common road.
- ② Suitable for high speed on good road surface application, with excellent anti-wet property and sideslip resistance.
- ③ Super anti-impact force and radiating performance.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]



# TRACMAX

# GRT967



- ① Application: Drive Wheel, Suitable for highway and common road.
- ② With Super driving performance and braking performance, high wear-resistance and low heat generation.
- ③ Excellent traction, heavy loading ability, longer mileage.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]



# GRT939



- ① Application: Steer Wheel for long distance, also can be used on Trailer Wheel. Suitable for highway and common road.
- ② Extra anti-side and wet skid resistance, good radiating performance.
- ③ Super anti-irregular wearing performance, adaptability to high-speed running, low noise.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]



# TRACMAX

# GRT907



- ① Application: Drive Wheel, Suitable for highway and common road.
- ② With Super driving performance and braking performance, high wear-resistance and low heat generation.
- ③ Good anti-wear and puncture attributes, super anti-impact face, radiating performance.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]









GRT90I

- 1Application: All position, suitable for all kinds of road conditions.
- 2Super wear ability and heat radiating performance, outstanding breaking and driving performance with heavy loading ability.
- 3Suitable for short-medium-long distances on paved or unpaved roads.



Standard Wheel Permitted Wheel Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/PSI)				
R90101	11R22.5 146/143M	16	15.5	8.50	279	1050	830	-	-	-	-
R90102	295/80R22.5 152/149M	18	15.5	9.00	298	1044	900	-	-	-	-
R90103	12R22.5 152/149M	18	16.5	9.00	300	1084	850	-	-	-	-
R90104	315/80R22.5 156/150M	20	19.0	9.00	312	1076	850	-	-	-	-
R90105	13R22.5 154/151K	18	21.5	9.75	320	1124	875	-	-	-	-









GRT957

- 1Application: Drive wheel, suitable for rough and common roads.
- 2Unique tread belt structure, tire tread compound with high wear -resistance and low heat generation.
- 3Special compounds for cut resistance, excellent traction, high anti-impact force.



Standard Wheel Permitted Wheel Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/PSI)				
T95701	11R22.5 146/143M	16	21.5	8.25	279	1050	830	-	-	-	-
T95702	295/80R22.5 152/149M	18	21.5	9.00	298	1044	850	-	-	-	-
T95703	12R22.5 152/149M	18	21.5	9.00	300	1084	850	-	-	-	-
T95704	315/80R22.5 156/150M	20	21.5	9.00	312	1076	850	-	-	-	-
T95705	13R22.5 154/151K	18	21.5	9.75	320	1124	875	-	-	-	-









GRT901

- 1Application: All position, suitable for all kinds of road conditions.
- 2Super wear ability and heat radiating performance, outstanding breaking and driving performance with heavy loading ability.
- 3Suitable for short-medium-long distances on paved or unpaved roads.



Standard Wheel Permitted Wheel Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/PSI)				
T90101	7.00R16 118/114L	14	12.5	5.50	198	778	770	-	-	-	-
T90102	7.50R16 122/118L	14	12.5	6.50	215	805	770	-	-	-	-
T90103	8.25R16 128/124K	16	14.0	6.50	235	855	770	-	-	-	-
T90104	9.00R20 144/142K	16	15.0	7.00	259	1019	900	-	-	-	-
T90105	10.00R20 149/146L	18	16.0	7.50	278	1054	930	-	-	-	-
T90106	11.00R20 152/149L	18	16.5	8.00	293	1085	930	-	-	-	-
T90107	12.00R20 154/151L	18	17.0	8.50	315	1125	830	-	-	-	-
T90108	12.00R24 160/157K	20	15.5	8.50	315	1226	900	-	-	-	-







## GRT928



- ❶ Application: Drive wheel, suitable for common roads paved with mixed materials.
- ❷ With super driving and braking performance, good resistance to wear and tear.
- ❸ High loading capability.



⦿ Standard Wheel    ⦿ Permitted Wheel    ✗ Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/PSI)				
T92801	7.00R16 118/114L	14	14.5	6.00	198	778	770	-	-	-	-
T92802	7.50R16 122/118L	14	14.5	6.00	215	805	770	-	-	-	-
T92803	8.25R16 128/124K	16	15.5	6.50	235	855	770	-	-	-	-
T92804	9.00R20 144/142K	16	18.5	7.00	259	1019	900	-	-	-	-
T92805	10.00R20 149/146L	18	19.0	7.50	278	1054	930	-	-	-	-
T92806	11.00R20 152/149L	18	20.0	8.00	293	1085	930	-	-	-	-
T92807	12.00R20 154/151L	18	21.0	8.50	315	1125	830	-	-	-	-







GRT956



- 1Application: Steer Wheel for short-medium distance, Suitable for highway and common road.
- 2Extra braking performance, excellent drainage and traction performance.
- 3Good stability and self cleaning capacity in rain days.



Standard Wheel Permitted Wheel Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/PSI)				
T95601	*215/75R17.5 126/124M	16	12.0	6.00	222	761	860	-	-	-	-
T95602	*235/75R17.5 132/130M	18	12.5	6.75	242	792	875	-	-	-	-
T95603	*245/70R19.5 136/134M	18	13.0	7.50	249	832	875	-	-	-	-
T95604	*265/70R19.5 140/138M	18	13.5	7.50	259	866	850	-	-	-	-
T95605	*275/70R22.5 148/145M	16	14.0	8.25	276	958	900	-	-	-	-
T95606	*295/80R22.5 152/149M	18	14.5	9.00	298	1044	850	-	-	-	-
T95607	315/70R22.5 154/150M	18	14.5	9.00	312	1014	900	-	-	-	-
T95608	*315/80R22.5 156/150M	20	14.5	9.00	312	1076	850	-	-	-	-

\* New Developing Sizes









GRT969

- ❶Application: Drive wheel, suitable for common roads and roads paved with mixed materials.
- ❷With super driving and braking performance, high speed performance, low noise and long mileage.
- ❸Excellent traction and adhesion, high wear-resistance and high loading capability.



Standard Wheel Permitted Wheel Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section Width (mm)	OA Diameter (mm)	Max. Pressure (kpa/PSI)				
T96901	*215/75R17.5 126/124M	14	15.0	6.00	222	761	700	-	-	-	-
T96902	*235/75R17.5 132/130M	16	15.0	6.75	242	792	775	-	-	-	-
T96903	*245/70R19.5 136/134M	16	16.0	7.50	249	832	830	-	-	-	-
T96904	*265/70R19.5 140/138M	16	16.0	7.50	259	866	830	-	-	-	-
T96905	*275/70R22.5 148/145M	16	20.0	8.25	276	958	900	-	-	-	-
T96906	*295/80R22.5 152/149M	18	20.5	9.00	298	1044	850	-	-	-	-
T96907	315/70R22.5 154/150M	18	19.5	9.00	312	1014	900	-	-	-	-
T96908	*315/80R22.5 156/150M	20	21.5	9.00	312	1076	850	-	-	-	-

\* New Developing Sizes





- ❶ Application: All Position Wheels for long distance.
- ❷ New designed pattern, Suitable for well paved road condition with excellent durability.
- ❸ Standard load, Low heat build-up, High speed.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

# TRACMAX



# TRACMAX

# GRT959



- ➊ Application: Drive wheel, suitable for common roads and rough way.
- ➋ Extra braking performance and deep groove, offer excellent traction and adhesion performance.
- ➌ Good anti-wear and puncture attributes, longer mileage.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]





- ① Application: Trailer Wheel, Suitable for highway and common road.
- ② With Super driving performance and braking performance, high wear-resistance and low heat generation.
- ③ Superior anti-irregular wearing performance, with extra anti-side and wet skid resistance, excellent safety and comfort riding.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]

\* New Developing Sizes



# TRACMAX

# GRT916



- ① Application: Trailer Wheel, Suitable for rough and common roads.
- ② Excellent traction and high wear-resistance.
- ③ Ultra strong ground adhesiveness on snow field and muddy roads.



 Standard Wheel  Permitted Wheel  Prohibited Wheel

[illegible]

\* New Developing Sizes





- ①Application: Trailer Wheel, Suitable for rough and common roads.
- ②Excellent traction and high wear-resistance.
- ③Ultra strong ground adhesiveness on snow field and muddy roads.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]


\* New Developing Sizes



# TRACMAX

# GRT966



- 
- ➊ Application: Drive wheel, suitable for highway and common roads.
  - ➋ Unique tread belt structure, high wear-resistance and low heat generation, powerful gripping ability, good resistance to wear and tear.
  - ➌ High loading capability, High speed performance and long mileage.




 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]



# GRT989



- 
- ①Application: Suitable for the roads on the mine and mountain areas.
  - ②Designed to incorporate mixed pattern on treads and deep grooves that enable a high driving force and superior ground adhesion performance.
  - ③Protection against piercing, and outstanding ground adhesion performance.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]



# TRACMAX

# GRT986



- ①Application: Suitable for the roads on the mine and mountain roads.
- ②Ultra block pattern with deep grooves, extra-wide running surface, good anti-wear and anti-puncture attributes.
- ③Excellent adhesion performance, high loading capacity.



 Standard Wheel
  Permitted Wheel
  Prohibited Wheel

[illegible]





GRT956

- 1Application: Steer Wheel for short-medium distance, Suitable for highway and common road.
- 2Extra braking performance, excellent drainage and traction performance.
- 3Good stability and self cleaning capacity in rain days.



Standard Wheel Permitted Wheel Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/PSI)				dB
R95601	*11R22.5 144/142M	14	14.5	8.25	279	1050	720	-	-	-	-
R95602	*11R22.5 146/143M	16	14.5	8.25	279	1050	830	-	-	-	-
R95603	*11R24.5 146/143M	14	14.5	8.25	279	1104	720	-	-	-	-
R95604	*11R24.5 149/146M	16	14.5	8.25	279	1104	830	-	-	-	-
R95605	*295/75R22.5 144/141M	14	14.0	9.00	298	1014	760	-	-	-	-
R95606	*295/75R22.5 146/143M	16	14.0	9.00	298	1014	830	-	-	-	-
R95607	*285/75R24.5 144/141M	14	14.0	8.25	283	1050	760	-	-	-	-
R95608	*285/75R24.5 147/144M	16	14.0	8.25	283	1050	830	-	-	-	-

\* New Developing Sizes



# TRACMAX

NEW







## GRT979

- 1 Application: Drive Wheel for medium mileage loading series.
- 2 Close Shoulder designs, the block pattern offer excellent drive force and good braking performance on paved road condition.
- 3 Excellent load capability, Longer mileage, Super Durability.



Standard Wheel   Permitted Wheel   Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth (mm)	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/PSI)				
T97901	* 11R22.5 144/142M	14	20.5	8.25	279	1050	720	-	-	-	-
T97902	* 11R22.5 146/143M	16	20.5	8.25	279	1050	830	-	-	-	-
T97903	* 11R24.5 146/143M	14	20.5	8.25	279	1104	720	-	-	-	-
T97904	* 11R24.5 149/146M	16	20.5	8.25	279	1104	830	-	-	-	-
T97905	* 295/75R22.5 144/141M	14	18.5	9.00	298	1014	760	-	-	-	-
T97906	* 295/75R22.5 146/143M	16	18.5	9.00	298	1014	830	-	-	-	-
T97907	* 285/75R24.5 144/141M	14	18.5	8.25	283	1050	760	-	-	-	-
T97908	* 285/75R24.5 147/144M	16	18.5	8.25	283	1050	830	-	-	-	-

\* New Developing Sizes





Asian Tyre Sourcing



# LIMITED WARRANTY

## 1. WHO IS COVERED BY THIS LIMITED WARRANTY?

- (1). You are the authorized distributors from Tracmax Tyre.
- (2). Your tires bear the Department of Transportation prescribed tires identification numbers and are not branded "NA" (Not Adjustable) or "Blem" (Blemish), and
- (3). Your tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturer's or tire manufacture' s recommendations, and your tires were purchased within 3 years.

## 2. WHAT IS COVERED AND FOR HOW LONG?

Tracmax Tyre warrants that if a tire becomes unserviceable due to an eligible adjustable conditions during the tread life (defined below) within 3 years from the original date of manufacture. The tire will be replaced by an equivalent new tire. A replacement charge may be required in order to obtain a replacement tire (as defined below).Or, a credit can be granted based on tread remaining.

## 3. REPLACEMENT CHARGE?

For tires being removed from service due to a defect in manufacture' s workmanship or materials, but not within the first 2/32" wear, the replacement price will be calculated by multiplying the current selling price( or sale price if original invoice is available) by the percentage of original tread depth that has been worn from tire.

## 4. WHAT IS NOT COVERED?

This warranty does not cover tires that become unserviceable due to cuts, snag or punctures.

1. Conditions resulting from road hazards, such as impact damage, cuts, snag or punctures.
2. Conditions resulting from improper installation, wheel misalignment, or tire/wheel assembly imbalance.
3. Conditions or irregular wear resulting from consumer damage, such as improper tire and vehicle maintenance, misuse, abuse or accident.
4. Tires which have been repaired, retreaded, or reclaimed.
5. Tires worn beyond the Tread wear indicator.
6. Ride complaints after the first 25% tread wear.
7. Ozone or weather checking on tires over 3 years from the date of manufacture.

## 5. WHEN DOES THE WARRANTY END?

A tire has delivered its full original tread life and the new tire coverage of this warranty ends when the tread wear indicators become visible, or three(3) years from the date of original tire manufacture or new tire purchase date (without proof of purchase, date of manufacture will be used or determine age).

## 6. OBLIGATIONS

In order to be eligible for the limited Warranty Service, a Official Warranty Claim Form must be filled out and sent into Tracmax Tyre along with DOT number(s) and serial number(s) cut off from the tire, picture(s) of the tire and of the adjustable condition visibly marked on the tire.

## 7. DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

## 8. Remark

Proper vehicle and tire care is necessary to obtain the expected wear from a tire, It is your obligation to properly maintain your tires and the vehicle upon which they are mounted, including:

- (A) Operating your tires at the inflation pressure recommended by the vehicle manufacturer
- (B) Keep your tire/wheel assemblies in balance.
- (C) Maintain proper wheel alignment.

**Asian Tyre Sourcing**





# Asian Tyre Sourcing

[SALES@ASIANTYRESOURCING.COM](mailto:SALES@ASIANTYRESOURCING.COM)



TRACMAX